Per WWC: #9 - #3 sacks of cement used in well seal. 10. CAW 12/27/83

WATER WELL REPORT
STATE OF OREGON

#1

RECEIVED
DEC 23 1983
WATER RESOURCES DEPT.
SALEM, OREGON

LINC 368 State Well No. 6S/10W-30

State Permit No.

(1) OWNER:
Name Pixieland RV Park
Address Rt. 2 Box 224
City Otis State OR. 97368

(2) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary Air ☑ Driven ☐
Rotary Mud ☐ Dug ☐
Cable ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☑ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐
Thermal: ☐ Withdrawal ☐ Reinjection ☐

(5) CASING INSTALLED:
Steel ☐ Plastic ☐
Threaded ☐ Welded ☐
6" Diam. from +1 ft. to 49 ft. Gauge .250
" Diam. from ft. to ft. Gauge

LINER INSTALLED:
4" Diam. from 0 ft. to 120 ft. Gauge .173

(6) PERFORATIONS:
Perforated? ☑ Yes ☐ No
Type of perforator used Mills Knife
Size of perforations ¼ in. by 2½ in.
124 perforations from 22 ft. to 49 ft.
PVC 70 perforations from 50 ft. to 120 ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☑ No
Manufacturer's Name
Type Model No.
Diam. Slot Size Set from ft. to ft.
Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☑ Yes ☐ No If yes, by whom? Paul Dickerson
Yield: 10 gal./min. with 45 ft. drawdown after 1 hrs.
" " " "
Air test gal./min. with drill stem at ft. hrs.
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Special standards: Yes ☐ No ☑
Well seal—Material used CEMENT GROUT
Well sealed from land surface to 21 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal sacks
How was cement grout placed? PRESSURE GROUTED
Was pump installed? YES Type HP Depth ft.
Was a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☐ No
Type of Water? depth of strata
Method of sealing strata off
Was well gravel packed? ☑ Yes ☐ No Size of gravel: 3/16
Gravel placed from 0 ft. to 120 ft. AROUND LINER

(10) LOCATION OF WELL:
County LINCOLN Driller's well number 1
¼ ¼ Section 30 T. 6S R. 10W W.M.
Tax Lot # Lot Blk Subdivision
Address at well location: SAME

(11) WATER LEVEL: Completed well.
Depth at which water was first found 19 ft.
Static level 10 ft. below land surface. Date
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 6"
Depth drilled 120 ft. Depth of completed well 120 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
BROWN CLAY	0	10	
GRAVEL & SAND	10	35	
SAND STONE	35	105	
CLAY STONE	105	120	

Work started 8-8 19 83 Completed 8-14 1983
Date well drilling machine moved off of well 8-15 1983

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Paul Dickerson (Drilling Machine Operator) Date 8/16, 1983.
Drilling Machine Operator's License No. 549

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name DICKERSON WELL DRILLING (Person, firm or corporation) (Type or print)
Address 14005 ORCHARD KNOB RD., DALLAS, OR.
[Signed] Paul E. Dickerson (Water Well Contractor)
Contractor's License No. 689 Date 8/16, 19 83

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

SP*12658-690